- ,DDORRQNOVWNVQVXRRQQNQ KPQQWDSSQ
- WDXORRRPPWXNQQXRORPQRWXWODXQ
- 7SORRVLQVWODDWRQWDORRPXQRWWDSV WDQXQNDVWPWXWDORWOXQ
- **4-Standen automatische pinole voeding en afslag met electromagnetische koppeling en boordiepte instelling.**
- PRWRXVKRRWXQVWOOLQRSVSDQWDIO
- XWDORRXSWDIOXQ
- **uime opspantafel met T-sleuven en koelmiddelafvoer, draaibaar om kolom met hoogte en 45 hoekinstelling.**
- 7DSIQFWLXVVWDQDD

Standard Equipment

tapping unit, protective shield, work lamp, coolant system, operating tools, operator manual

Options	Part No.
• PB 100 V-Block Drill Press Vise	104840
• Reduction Sleeve MT 4/2	103825
• Mounting Shaft MT 4	108641

For additional options for this machine, visit our website and search for SSB F Super (Product Search)

Digital display and ergonomically positioned controls ensure maximum user comfort

Specifications		SSB 40 F Super	SSB 50 F Super
Working area			
Drilling capacity	mm	40	50
Tapping capacity, steel		M 24	M 30
Table set up area	mm	540x440	580x460
Quill stroke	mm	190	200
Manual table travel	mm	570	530
Powered table travel	mm	430	410
Table swivel range (max.)		± 45°	± 45°
Column diameter	mm	140	180
Spindle nose-to-table distance (max.)	mm	665	590
Spindle nose-to-foot distance	mm	1.195	1.175
Throat	mm	340	360
Headstock			
Speed range	1/min	60 - 2.600	50 - 2.200
Spindle mount		MK 4	MK 4
Feed			
Quill feeds	mm/R	0,1; 0,2; 0,3; 0,4 (4)	0,08; 0,12; 0,17; 0,24; 0,35; 0,50 (6)
Drive capacity			
Motor rating / voltage	kW/V	2 / 400	3 / 400
Measures and weights			
Overall dimensions (length x width x height)	m	1x0,65x2,22	1,15x0,68x2,36
Weight	kg	500	650
Part No.		162335	101669