

KKS 315 T is shown



- Easy operation, rugged design, and precise angular cuts make this circular cold saw a “must-have” basic for any workshop
- The models KKS 250 and 275 T provide a rigid vise with quick-action clamping feature and are ideal for small batch productions
- KKS 315 T / KKS 350 T feature a self-centering dual vise that hold the workpiece firmly on both sides of the saw blade
- The miter can be adjusted up to +/- 45 degrees by rotating the gear head
- All models have high-torque motors, and the KKS 315 and 350 T also have reversible poles and 2 speeds
- An integrated coolant system is part of the standard equipment on all models

### Standard Equipment

self centering double vise (KKS 315 / 350 T), quick-action vise (KKS 250 / 275 T), base, coolant system, 1 saw blade, linear stop



Dual vise (KKS 315 / 350 T)

### Options

### Part No.

• Circular Saw Blade / KKS 250 (pitch 6)	109802
• Circular Saw Blade / KKS 315 (pitch 6)	109808
• Circular Saw Blade / KKS 350 (pitch 5)	109809
• Circular Saw Blade / KKS 275 (pitch 6)	109810

Price on request

### Specifications

		KKS 250 T	KKS 275 T	KKS 315 T	KKS 350 T
<b>Working area</b>					
Max. saw blade diameter	mm	250	275	315	350
Shaft diameter	mm	32	32	40	32
Speed	1/min	42	42	18/36	18/36
Width of vise	mm	100	100	145	145
Working height	mm	960	960	960	960
<b>Cutting capacities</b>					
Cutting capacity 90° - round	mm	60	70	100	120
Cutting capacity 90° - square	mm	55	65	100	110
Cutting capacity 90° - flat	mm	75x45	90x45	140x90	140x100
Cutting capacity 45° (round) L	mm	55	65	90	105
Cutting capacity 45° (square) L	mm	50	60	90	100
Cutting capacity 45° (flat) L	mm	55x45	70x45	100x90	100x100
Cutting capacity 45° (round) R	mm	55	65	90	105
Cutting capacity 45° (square) R	mm	50	60	90	100
Cutting capacity 45° (flat) R	mm	55x45	70x45	100x90	100x100
<b>Drive capacity</b>					
Main motor rating	kW	1,1	1,1	0,75 / 1,3	0,75 / 1,3
Supply voltage	V	400	400	400	400
<b>Measures and weights</b>					
Overall dimensions (length x width x height)	m	0,92x0,48x1,71	0,92x0,48x1,78	0,92x0,56x1,78	0,97x0,56x1,83
Weight	kg	143	148	227	236
Part No.		102119	102118	102120	102121